


LINDA



POTENZA W	KELVIN	LUMEN APPARECCHIO lm	LUMEN SORGENTE lm	FASCIO °	MISURE mm	CODICE	EAN	CLASSE ENERGETICA
16-20-24	3000-4000-6500	1600-2000-2400	2300-3000-3300	120	1	LINDA24KP	8031453034535	A ↑ G E
24-28-32	3000-4000-6500	2400-2800-3200	3300-3800-4400	120	2	LINDA32KP	8031453034573	A ↑ G E
32-36-40	3000-4000-6500	3200-3600-4000	4400-5000-5500	120	3	LINDA40KP	8031453034542	A ↑ G E
40-44-48	3000-4000-6500	4000-4400-4800	5500-6200-6800	120	4	LINDA48KP	8031453034580	A ↑ G E



Ø B



DIMENSIONI	A	B	C
1	22	283	
2	22	383	
3	24	483	
4	24	583	

- Plafoniera ultrasottile in policarbonato, ideale per interni
- Installazione facilitata con fissaggio a slitta
- Tre modalità di funzionamento: downlight, illuminazione indiretta e biemissione selezionabili tramite interruttore
- Illuminazione indiretta 3000K
- In opzione kit per installazione a sospensione
- Potenza e CCT selezionabili



A